



# Codec

<b>Style</b>	<b>Tufted 1/10" Gauge Loop Pile Tile</b>
<b>Yarn Construction</b>	<b>100% Solution Dyed Nylon</b>
<b>Pile Yarn Weight</b>	<b>600gsm</b>
<b>Pile Height</b>	<b>3mm</b>
<b>Total Weight</b>	<b>4390gsm</b>
<b>Total Thickness</b>	<b>6mm</b>
<b>Backing</b>	<b>100% Envirobase - minimum of 75% recycled material</b>
<b>Additional Backing</b>	<b>Komfort Bac available on request</b>
<b>Tile Size</b>	<b>50cm x 50cm</b>
<b>Tiles Per Box</b>	<b>20 (5m<sup>2</sup>)</b>
<b>Wear Classification</b>	<b>Heavy Contract Class 33</b>
<b>Luxury Class</b>	<b>LC1</b>
<b>Anti-Static</b>	<b>Suitable for use with computers. Less than 2Kv</b>
<b>Colour Fastness</b>	<b>Light (BS EN ISO 105:B02) &gt;5 Shampoo (BS 1006:UK-TB:1990) 4-5 Dry Rubbing (BS EN ISO 105:B01) 4-5 Wet Rubbing (BS EN ISO 105:X12) 4-5</b>
<b>Flammability</b>	<b>BS5287 Assessment and labelling of Textile Floorcovering tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char</b>
<b>BS EN 13501</b>	<b>Class Bfl-s1</b>
<b>Impact Noise Reduction</b>	<b>26dB</b>
<b>Castor Chair Test</b>	<b>Suitable for intensive use with castor chairs</b>
<b>Warranty</b>	<b>10 years</b>
<b>VOC Content</b>	<b>E1 in relation to EN 14041:2004</b>
<b>Environmental Status</b>	<b>BREEAM® A Rated</b>



MADE IN BRITAIN



Please note, for technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Paragon Carpet Tiles reserves the right to change or modify product specifications without giving prior notice.



A Division of National Floorcoverings Ltd.  
Farfield Park, Manvers, Wath-upon-Deerne,  
Rotherham, S63 5DB  
www.paragon-carpets.co.uk

T: +44(0) 1709 763839  
E: sales@paragon-carpets.co.uk  
Samples Department: +44(0) 1709 763805  
E: samples@paragon-carpets.co.uk