



General data

Panel		580 x 145 mm
Total thickness	EN14354	± 13,5 mm
Numbers of panels per pack		12 (6xA & 6xB)
m² per pack		1,009 m²

Panel build up

1. Finishing	UV cured Lacquer	Anti-scratch top coat	5 - 7 layers
2. Toplayer		PEFC controlled sources	2,5 (±0,5) mm
3. Core board		PEFC controlled sources	Wooden core
4. Backing layer		PEFC controlled sources	2 mm
Tongue and groove		Wood Veneer	Uniclic
		Length	Uniclic
		Width	Uniclic



Warranty

Domestic use	Conditions in each pack	Lifetime
Uniclic		Lifetime
Commercial		On request
"Wood for Life" Edge Protect +	See warranty conditions	15 years
"Wood for Life" Surface & Edge Protect + (lacquered products only)	See warranty conditions	15 years

Surface layer

Wood species	Oak
Origin	Europe
Natural variance	Due to nature, visual surface can deviate from samples
Surface treatments	cf catalogue / website

Installation

		Norm requirements
Floating	On Quick-Step underlay	cf installation instructions
Glued to subfloor	Quick-Step MS polymer resin	cf installation instructions
General aspect of installed flooring		EN 14354 - Table 1
Dimensional stability	ISO 24339	Changes 30 - 85 % RH
Underfloor heating	Suitable	cf special installation instructions

Classification properties

Stain resistance	EN 13442		class 3
		Floors with "Wood for Life" Surface Protect + (Lacquered only)	class 5
CE	EN 14342:2013	Notified Body	NB 0766 - EPH Dresden
UKCA	EN 14342:2013	Approved Body	AB 0321 - Satra UK
Castor chairs	ISO 4918	Tested with underlay	25.000
Slip resistance	CEN / TS 15676 : 2008	Dry Pendulum test	Depending on structure and surface treatment
Emission of formaldehyde	EN 717-1		≤ E1
PCP	CEN / TR 14823:2004		≤ 5 ppm
Thermal resistance	EN12664:2001		0,14 m².K / W
Reaction to fire	EN 13501-1		Dfl-s1

Ecological certificates

AFFSET	A+	France
PEFC	PEFC / 07-32-37	
EPD	Available on request	
F4* Compliant		

